

## CTEK MXS 25 Smart 12 Volt Battery Charger

**POWERFUL AND EFFICIENT CHARGING FOR WORK AND LEISURE** The MXS 25 is a professional 12V charger. It offers efficient and fast charging and is ideal in workshops, caravans, RVs and boats. The MXS 25 is equipped with all necessary features and functions to solve a broad range of battery related problems.

Rating: Not Rated Yet

**Price**

Sales price \$ 585.00

[Ask a question about this product](#)

### Description

The MXS 25 is a professional 12V charger. It offers efficient and fast charging and is ideal in workshops, caravans, RVs and boats. The MXS 25 is equipped with all necessary features and functions to solve a broad range of battery related problems. It offers features such as battery diagnosis that shows if a battery can receive and retain a charge, a special reconditioning function that restores stratified and deeply discharged batteries, unique maintenance charging and a temperature sensor for optimised charging regardless of the weather conditions. It also has a power supply mode which allows the battery to be disconnected from the vehicle without losing important configurations.

The MXS 25 is a fully automatic 8-step charger that delivers 25A to 12V batteries from 40–500Ah. The charger is IP 44 classified (outdoor use), designed to protect vehicle electronics and non-sparking, reverse polarity protected and short-circuit proof. It is delivered with a 2-year warranty.

Supplied with clamps, temp sensor on cable.

Auto: Fully automatic for optimal charging

12V: For all lead-acid batteries

Fully Charged Battery / Maintenance Charging

Temperature sensor

RECOND: Recondition of deeply discharged batteries

SUPPLY: Use the charger as a power supply

Model 1055  
number

## CTEK MXS 25 battery charger

---

Volt	12V
Rated Voltage	220–240VAC, 50–60Hz
AC	
Charging voltage	NORMAL: 14.4V, RECOND: 15.8V, SUPPLY: 13.6V
Min battery voltage	2.0V
Charging current	25A max
Current, mains	2.9A rms (at full charging current)
Back current drain	<1Ah/month
Ripple	<4%
Ambient temperature	-20°C to +50°C, output power is reduced automatically at high temperatures
Charger type	8 step, fully automatic charging cycle
Battery types	All types of 12V lead-acid batteries (WET, MF, Ca/Ca, AGM and GEL)
Battery capacity	40–500Ah up to 500Ah for maintenance
Dimensions	235 x 130 x 65mm (L x W x H)
Insulation class	IP44
Weight	1.9kg

Units in box: 1

### Reviews

There are yet no reviews for this product.